

EPS-1205 Economy Power Supply

- Approvals Include: UL listed
- 12 VDC, 500 mA, filtered, plugs into an AC outlet.
- Includes DC output cord with polarized plug.
- Economically powers AFT-100 AM/FM Tuner.

EPS-2401 Economy Power Supply

- Approvals Include: UL listed
- 24 VDC, 100 mA, filtered, plugs into an AC outlet.
- Powers 24 VDC alert signals and tone generators.
- B battery.

RPS-2406 Fully Regulated and Filtered

- Approvals Include: UL listed
- 24 VDC, 600 mA, wall mounting with 6 ft. AC power cord.
- Current limited, short circuit and overload protected with auto shutdown and reset.
- Power supply in non-UL fire alarm applications for Series DV-100 & DV-200 Voicelink Systems.
- A battery.

RPS-2440-A 24 VDC Dual Output

- Approvals Include: UL listed
- Either two 2 amp, or one 4 amp.
- Fully regulated and filtered.
- Each output with independent power on LED.
- Current limiting overload and short circuit protection.
- Auto shutdown and reset, AC circuit breaker for input protection.
- A battery.

PSC-2420-R Power Supply/Charger

- 24 VDC, 1-8 fused outputs.
- 20.8 amp switch mode designed with full regulation and filtering.
- Outputs are current limited, overload and short circuit protected.
- Equipped with a battery charger capable of handling a 60 ampere hour battery load.
- PSC-2420-R, red cabinet; (21" H x 16" W x 6" D, 26 lbs. 6 oz.).

DCI-24-24 Dry Contact Interface

- Approvals Include: UL Standard 2017 Listed
- Provides the power to operate a wide variety of Wheelock 24 VDC signaling products while isolating the load from the contact closure.
- Delivers 24 VDC at 300 mA via a dry contact closure.
- Can be wall-mounted, comes with six-foot power cord.
- Quick-connect input/output terminals require no special tools for hookup.
- Can power multiple Wheelock products.
- One DCI-24-24 can activate another DCI-24-24 to power additional products.
- Compatible Products: PS-33A, CH-AT2-W, CH-BT2, TB-592, UTA Series and MT-12/24-W



Series EPS-1205



Series EPS-2401



Series RPS-2406



Series RPS-2440-A



Series DCI-24-24

Specification and Ordering Information

Model Number	Order Code	Description	Output Voltage	Output Current	Regulation	Ripple & Noise
EPS-1205	4892	Filtered Power Supply	12 VDC	500mA	Non-Regulated	2.5 VP-P
EPS-2401	3545	Filtered Power Supply	24 VDC	100mA	Non-Regulated	10mVRMS
RPS-2406	3770	Regulated & Filtered Power Supply	24 VDC	600mA	+/- 5%	10mVRMS
RPS-2440-A	4839	Dual Output Regulated & Filtered Power Supply	24 VDC	4 Amps	+/- 5%	10mVRMS
PSC-2420-R	7377	Power Supply/Charger - Red cabinet (120 VAC)	24 VDC	20.8 Amps	+/- 5%	2% max, p-p
PSC-2420E-R	7385	Power Supply/Charger (220 VAC) (E=Export)	24 VDC	20.8Amps	+/- 5%	2% max, p-p
DCI-24-24	24 VDC	Dry Contact Interface	Input		Output	
			Dry Contact Closure		24 VDC (300 mA)	