

Description:

Wheelock telephone relays activate various appliances when a telephone ring voltage is detected. Three models are available to accommodate different voltage requirements, environments and applications.

Features:

- Approvals Include: UL Listed, FCC registered

CRT-T-40 Weatherproof AC/DC Relay

- Includes mounting bracket
- Hard wire connections
- Accepts RJ-11 phone plug
- Designed for analog phone lines

XRT-T-40 Explosion-Proof AC/DC Relay

- Hard wire connections
- Accepts RJ-11 phone plug
- Designed for analog phone lines

RX-1419 Telephone Relay

- Designed for analog phone lines or low voltage activations
- Screw terminal connections
- Accepts RJ-11 phone plug
- Includes AC line cord
- Replacement relay for 163 package



Series CRT-T-40



Series XRT-T-40



Series RX-1419

Specification and Ordering Information

Model Number	Order Code	Application	Input Voltage	AC Contact Ratings	DC Contact Ratings	REN
CRT-T-40	0049	Indoor/Outdoor	39-150 V, 20-30 Hz	Up to 230 VAC	Up to 115 VDC	0.6
XRT-T-40	0221	Explosion Proof	39-150 V, 20-30 Hz	Up to 230 VAC	Up to 115 VDC	0.6
RX-1419	0040	Indoor	39-150 V, 20-30 Hz	5A	115 VAC, 60 Hz	-
			18-48 VDC	2A	115 VAC, 60 Hz	0.6
			30-48 VAC	0.5A	115 VDC	-